

# Thermal Receipt Printer

With Auto-Cutter Function



- 1) Compatible with ESC/POS command.
- 2) Suitable for all types of commercial retail POS systems.
- 3) Support Bold printing / character adjusting / line spacing setting.
- 4) Supporting QR-code/Bar-code printing
- 5) Support different density bitmap graphics printed.
- 6) Support Multi-language printed.

## PRODUCT SPECIFICATIONS

<b>Interfaces</b>	USB / COM / Bluetooth 4.0/ WIFI ( Optional)
<b>Print Comand</b>	ESC/POS
<b>Print Method</b>	Thermal Line Printing
<b>Print Speed</b>	≤90mm/sec
<b>Print Resolution</b>	203dpi (8 dot/mm)
<b>Print Width</b>	72mm
<b>Line Spacing</b>	3.75mm (Adjustable by commands)
<b>TPH Life</b>	50KM
<b>MCBF</b>	5 Million Lines
<b>Column Capacity</b>	576 dots/line
<b>Character Size</b>	ASCII , Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)
<b>Barcode Type</b>	1D:UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/ CODE93/CODE128 2D: QR CODE / PDF417
<b>Compatible OS</b>	Window Systems ; Android & IOS Operate Systems
<b>Paper</b>	
<b>Paper Type</b>	Roll Paper
<b>Paper Width</b>	80mm
<b>Line Spacing</b>	3.75mm (Adjustable by commands)
<b>Roll Diameter</b>	φ≤45mm
<b>Paper Thickness</b>	0.06-0.08mm
<b>Electrical</b>	
<b>Li-Battery</b>	7.4v DV/2000mA (Re-chargeable lithium battery)
<b>Power Supply</b>	Input: AC 110V/240V, 50~60Hz ; Output: DC 9V/2A
<b>Standby Time</b>	4 days after fully charged
<b>Continuous Printing</b>	120 pieces Thermal Roll for fully charged battery
<b>Physical</b>	
<b>Printer Dimension</b>	10.8*10*4.6cm
<b>Unit Weight</b>	350g (including accessories: lithium-ion batteries, cable, test paper)
<b>Carton Size</b>	48x43x35cm
<b>GW per carton</b>	22kg (40pcs/CTN)
<b>Color</b>	Black